

| Collection | Finish | Product |
|------------|----------------|-------------------------|
| Penthouse | Polished Brass | 2 & 5Amp Socket Outlets |

Penthouse Collection 2 & 5Amp Socket Outlets







Specified in Polished Brass

Description

A range of round pin socket outlets have been designed for ease of installation, all having the superior quality and design features of The Penthouse Collection.

Standards, Approvals & Directives

Comply with BS 546.

Features

- Top access terminals making wiring easier and quicker.
- Shutter safety feature.
- · Terminal marking present on socket housing for clearer identification.
- Black and White housings available to compliment plate finishes
- Automatic primary switching on insertion of plug

Availability

Our 2amp and 5amp un-switched sockets are available in Black and White polycarbonate moulded housings and are supplied as interiors with grids throughout the Classic, Infinity, Dimension, Crystal, Heritage and Penthouse Collections.

All plate finishes available. Please see the Wandsworth catalogue for more information.

Applications & Uses

Our 2amp and 5amp socket outlets can be used for lighting circuits that demand low amperages.

Ordering

When ordering please state the catalogue number and finish of the required socket outlet.

Catalogue Numbers

Interiors

A4151/* - 2amp Socket Outlet

A485/* - 5amp Socket Outlet

Plates

P4151/* - 2amp Plate

P485/* - 5amp Plate

Flush Box

1702/G (42mm deep)


*Interior Finishes available:


/B - Black, /W - White



| Collection | Finish | Product |
|------------|----------------|-------------------------|
| Penthouse | Polished Brass | 2 & 5Amp Socket Outlets |

Side view common to all sizes





2amp Socket Outlet

Depth:

2amp Socket - 16mm

Recommended Box Depth:


Metal boxes to BS4662

1.5 mm2 Cable – 25mm Box

2.5 mm2 Cable – 35mm Box

Not suitable for dry liner/fast fix or surface boxes.

Side view common to all sizes





5amp Socket Outlet

Depth:

5amp Socket – 19mm

Recommended Box Depth:

Metal boxes to BS4662

5amp Socket – 35mm Box

Not suitable for dry liner/fast fix or surface boxes.

| Technical Specification | | | | |
|-------------------------------|---|---|--|--|
| Supply Voltage | 2 Way - 20 Amp | | | |
| Terminal Capacities: | 2amp Socket | 5amp Socket | | |
| | Live, Neutral & Earth $1 \times 2.5 \text{ mm}^2$ $2 \times 2.0 \text{ mm}^2$ $2 \times 1.5 \text{ mm}^2$ $4 \times 1.0 \text{ mm}^2$ | Live, Neutral & Earth $1 \times 2.5 \text{ mm}^2$ $2 \times 2.0 \text{ mm}^2$ $2 \times 1.5 \text{ mm}^2$ $4 \times 1.0 \text{ mm}^2$ | | |
| Ambient Operating Temperature | -5°C to +40°C | | | |
| IP Rating | IP2XD | | | |
| Max Installation Altitude | 2000 meters | | | |

NOTE

The Company Policy is one of continuous improvement and the right to change designs, dimensions, descriptive matter, etc., at any time without notice is reserved.